

DESCRIPTION

UNIPATCH is a fast-setting Portland cement and polymer based interior floor-patching compound. It patches and fills cracks and irregularities in concrete and exterior grade plywood in preparation of vinyl installation, linoleum, wood parquet flooring, ceramic tile, slate, marble and stone.

Can be mixed with UNIPATCH PLUS to provide higher bond strength on surfaces.

CHARACTERISTICS

- Quick set
- Strong stand
- Easy to use

TECHNICAL DATA @ 22 C

Meets or exceeds standard norms:
CGSB 71-GP-30M, Type 2 ANSI A118.4

Pot life	10 minutes
Initial set	20 minutes
Final set	60-90 minutes
Compression force	1000 psi (7 days) 3000 psi (28 days)
Colour	Gray
Coverage	54 sq-ft / 11 kg @ 1/16 thickness

FORMATS

4.5kg (10lbs)
11.33kg (25 lbs)

TILE AND STONE INSTALLATION SYSTEMS

- Self-levelling
- Thinset mortar
- Adhesive
- Cement grout
- Water-based epoxy grout
- Waterproofing
- Acoustic adhesive
- Sealers
- Cleaners
- Strippers
- Colorants



Manufactured by La Margna Inc.
412, avenue St-Sacrement
Québec (Qc)
G1N 3Y3

Tel: 418-688-8286, toll free 1-800-463-6850
Fax: 418-688-2070, toll free 1-800-419-4819
www.profixsystems.com



How to use patching mortar



PROFIX COMMITMENT



La Margna Inc., as the exclusive manufacturer of PROFIX tile and stone installation products and PROTHERM radiant floor systems, is committed to offering you superior quality products that meet or surpass industry standards which are established by the "Terrazzo, Tile & Marble Association of Canada" (TTMAC) and by the "Tile Council of North America" (TCA).

Using strict quality control standards in our production, we ensure that you get the very best products for the best results possible. Furthermore, thanks to our research & development laboratory and a qualified research team, La Margna inc. is constantly refining its technology to offer the best performance at the best price.

All PROFIX products are guaranteed to offer optimum performance when they are used during installations that conform to the standards established by the TTMAC, TCA and La Margna.

La Margna inc. stands by its products and offers excellent technical support for your projects, with complete products specifications and installation techniques. No matter the size of your project, whether you are an architect, store owner or contractor, the PROFIX team is available for you. So don't hesitate to contact our PROFIX technical support service. Trust PROFIX products for excellent long lasting results.

We thank you for choosing PROFIX quality products for your next project.

HOW TO APPLY UNIPATCH?

A patching mortar is used to repair wood and cement areas before applying a floor covering.



Step 1

Use a clean container, mix 1 part of water to 3 parts of UNIPATCH. Pour the water first and gradually add UNIPATCH powder while mixing. If used in small quantities, ensure the dry powder in the bag is well mixed. Avoid prolonged mixing

that will reduce the pot life of the product.



Step 2

Mix to a smooth lump free, creamy paste consistency. Do not mix more material than can be applied in 10 minutes. Avoid prolonged mixing that will reduce the pot life of the product.



Step 3

Do not let it sit. Spread onto the floor surface immediately after mixing. Spread with a flat steel trowel to the desired finish. The floor finish may be applied as soon as the UNIPATCH is completely dry (60-90 minutes).



Step 4

Clean tools and hands before the patching mortar gets dry.

USE UNIPATCH BEFORE...


Installing your ceramic tile...



Installing your carpet...



Installing your wood...



Installing your vinyl...

