

Material Safety Data Sheet (MSDS)

Read msds sheet before use of product

AQUAT XT GROUT & TILE SEALER

SECTION 1: General Information

Manufactured By: LA MARGNA INC / SANITEN
412 St-Sacrement
Québec, (PQ)
G1N 3Y3
(Canada)

Contact : 1-800-838-4237 or 1-418-688-2070

Website: WWW.PROFIXSYSTEMS.COM

E-mail : INFO@PROFIXSYSTEMS.COM

In case of chemical emergency involving a spill, leak, fire, explosion, exposure or accident, contact the following:
CANUTEC (Canada) 1-613-996-6666 CHEMTREC (United-States) 1-800-424-9300

SECTION 2: Physical Characteristics

PHYSICAL APPEARANCE :	MILKY LIQUID
P.H.:	8.5
VAPOUR DENSITY:	N/A
BOILING POINT:	100 °C
SOLUBILITY IN WATER:	SOLUBLE
ODOUR:	MILD
VISCOSITY (1 WATER):	0.93

SECTION 3 : Danger Evaluation

DAINGEROUS INGREDIENTS	%	CAS Number	LD ₅₀ (SPECIES + ROUTE)	CL 50 (SPECIES)
DIETHYLENE GLYCOL MONOBUTYL ETHER	10-20%	00111-77-3	4300 mg/kg (r/o)	6700ppm R/4Hrs

SECTION 4 : Transport

W.H.M.I.S.
CLASS: D2 B

SECTION 5 : Reactivity Data

STABILITY: STABLE MATERIALS TO AVOID: N/A

CONDITIONS TO AVOID: N/A

DECOMPOSITION HAZARD FROM BY-PRODUCTS: N/A

SECTION 6 : Health Hazard Data

ABSORPTION MODES DURING HANDLING

INHALATION? YES THROUGH SKIN? YES INGESTION? YES

Acute effects :

CONTACT CAN CAUSE REDNESS AND IRRITATION
CAN CAUSE IRRITATION, NAUSEA AND DIARRHEA

Chronic effects :

CANCER: NOT DANGEROUS AS PER WHMIS
IRRITANCY OF MATERIAL DANGEROUS AS PER WHMIS

INGESTION IS EXTREMELY DANGEROUS

SECTION 7 : Emergency and First Aid Measures

SKIN CONTACT	Wash thoroughly with running water. Seek medical attention if irritation persists.
INHALATION	Move the person to a well vented area and give fresh air. Seek medical attention.
EYE CONTACT	Flush with running water, be sure to flush under eyelids, seek immediate medical attention.
INGESTION	Do not induce vomiting. Rinse mouth thoroughly and give a glass of water. In case of spontaneous vomiting, bend down to prevent risk of inhaling. Never give anything to drink to an unconscious person.

SECTION 8 : Safe Use and Storage

IN CASE OF SPILL OR LEAKAGE :	Absorb small spills with an inert absorbent material. Prevent large spills from flowing into sewers and water ways.
WASTE DISPOSAL METHOD :	Follow all Federal, Provincial and Local regulations.
HANDLING AND STORAGE :	In closed containers, in a dry, cool and well ventilated area.
ADDITIONAL PRECAUTIONS :	Wear appropriate equipment. Keep container closed when not in use.

SECTION 9: Control Measures

RESPIRATORY PROTECTION :	Normally not required
VENTILATION	
LOCAL :	Normal ventilation is generally adequate.
EYE PROTECTION :	Chemical safety goggles.
PROTECTION GLOVES :	Neoprene or rubber
OTHER PROTECTION ACCESSORIES OR CLOTHING :	Wear a rubber apron or standard work clothes.

SECTION 10 : Fire and explosion hazards

FLASH POINT	EXPLOSIVE INFERIOR LIMIT (%)	EXPLOSIVE SUPERIOR LIMIT (%)
167°C	N/A	N/A
EXTINGUISHING MEDIA :		
N/A		
SPECIAL CONDITIONS THAT MAY CAUSE FIRE OR EXPLOSIONS :		
N/A		
SPECIAL FIRE FIGHTING PROCEDURES : N/A		

This MSDS sheet is valid for a period of three (3) years following the date inscribed bellow

MSDS sheet prepared by : Christian Houle

Date : 01 / 01 / 2010

La Margna Inc considers that all the information contained in this msds sheet is accurate. We do not offer however, any warranty regarding the exactitude of this data or upon the results to be obtained from using the product. La Margna Inc. assumes no responsibility regarding personal injuries or property damage to vendees, users or third parties caused by the material. The vendor or users assume all risks associated with the use of any product sold by La Margna Inc.