

POLY500

 Polymer-modified Sanded Grout (Made with Portland Cement)

SECTION 1: General Information

Manufactured By: LA MARGNA INC
412 St-Sacrement
Québec, (PQ)
G1N 3Y3
(Canada)

Contact : 1-800-838-4237 or 1-418-688-2070

Website: WWW.PROFIXSYSTEMS.COM

E-mail : INFO@PROFIXSYSTEMS.COM

In case of chemical emergency involving a spill, leak, fire, explosion, exposure or accident, contact the following:
CANUTEC (Canada) 1-613-996-6666 CHEMTREC (United-States) 1-800-424-9300

SECTION 2: Physical Characteristics

| | |
|------------------------------|------------------------|
| Physical appearance : | Powder (Grey or White) |
| Vapour pressure: | N/A |
| Vapour density: | N/A |
| Boiling point: | N/A |
| Freezing point: | N/A |
| P.H.: | N/A |
| Solubility in water: | Soluble |
| Odour: | Odourless |
| Evaporation rate: | N/A |
| Specific Gravity: | N/A |

SECTION 3 : Danger Evaluation

| Dangerous Ingredients | % | CAS Number | LD ₅₀ (SPECIES + ROUTE) | CL 50 (SPECIES) |
|------------------------------|------------|------------|---------------------------------------|--------------------|
| HYDRAULIC CEMENT | 25-35 % | 65997-15-1 | 10.0 Mg/M ³ | Total dust |
| CALCIUM OXYDE | 0.2-0.9 | 1305-78-8 | N/A | N/A |
| CRYSTALLINE SILLICA (QUARTZ) | 45-55 % | 14808-60-7 | 0.1 mg/M ³ | Breathable dust |
| MAGNESIUM OXYDE | 0.35-3.0 % | 1309-48-4 | N/A | N/A |

SECTION 4 : Transport

By Sea : N/A

By Air : N/A

By Grounds : N/A

Other : N/A

SECTION 5 : Reactivity Data

Stability:

Store Dry. Hydrates with water and is partly soluble in acids

Materials to avoid:

Avoid contact with mineral acids and strong oxidizing agents.

Conditions to avoid: Hydrates with water and is partly soluble in acids

Decomposition hazard from by-products:

CO, CO₂, acetic acid, hydrocarbon fragments.

Polymerisation : Will not occur.

SECTION 6 : Health Hazard Data

Absorption modes during handling

Inhalation? Yes Through Skin? Yes Ingestion? Yes

Acute effects :

The LD 50 of the mixture has not been determined, but the mixture is not expected to be acutely toxic by inhalation. Inhalation of high concentrations will cause irritation and can cause alkaline burns of the mouth, throat and respiratory passage and may lead to chronic effects. The mixture has not been tested on laboratory animals. Based on the effects of components, contact with eyes will cause irritation and can result in alkaline burns if not flushed immediately with running water. The mixture has not been tested on laboratory animals. Based on the effects of components, prolonged or repeated contact may cause irritation. If skin is moist, irritation and alkaline burning can occur if area is not immediately flushed with running water. Not expected to be toxic by the dermal route. The oral LD 50 of the mixture has not been determined. Based on the effects of components, ingestion of large amounts can cause irritation and alkaline burning of the mouth and throat.

Chronic effects :

Portland cement dust can cause inflammation of the eyes and nasal passages. People with sensitive skin may experience an allergic reaction. In contact with water calcium hydroxide produces an alkaline liquid with a PH of 12 to 13, which can be a source of eye and skin irritation and burning, Inhalation or ingestion can cause irritation and burning of the mouth, throat and respiratory tract. Contains crystalline silica. Overexposure by inhalation to crystalline silica causes silicosis, an irreversible and progressive scarring of the lungs. Symptoms may include breathlessness, weakness and cough with sputum. May progress to respiratory and heart failure. The IARC classifies crystalline silica in Group 2A based on limited evidence for carcinogenicity to humans and sufficient evidence for carcinogenicity in animals.

Cancerogenicity :

The IARC classifies crystalline silica in Group 2A based on limited evidence for carcinogenicity to humans and sufficient evidence for carcinogenicity in animals. Portland cement dust can cause inflammation of the eyes and nasal passages.

Signs of overexposure :

Overexposure by inhalation to crystalline silica causes silicosis, an irreversible and progressive scarring of the lungs. Symptoms may include breathlessness, weakness and cough with sputum. May progress to respiratory and heart failure.

SECTION 7 : Emergency and First Aid Measures

| | |
|---------------------|--|
| Skin contact | Wash thoroughly with running water. Seek medical attention if irritation persists. |
| Inhalation | Move the person to a well vented area and give fresh air. Seek medical attention. |
| Eye contact | Flush with running water, be sure to flush under eyelids, seek immediate medical attention. |
| Ingestion | Do not induce vomiting. If person is conscious give lots of water to drink. Never force an unconscious person to drink water. Flush mouth and throat with water. Seek medical attention. |

SECTION 8 : Safe Use and Storage

| | |
|--------------------------------------|---|
| In case of spill or leakage : | May be slippery when wet. Avoid generating dust during pick up |
| Waste disposal method : | Contact local environmental agency to dispose in approved landfill. |
| Handling and Storage : | Store in dry sealed containers. |
| Additional precautions : | Wear appropriate equipment. |

SECTION 9: Control Measures

| | |
|---|--|
| Respiratory protection : | NIOSH/MSHA approved for crystalline silica and Portland cement. |
| Ventilation | |
| Local : | Closed system or local exhaust to prevent generation and inhalation of dust. |
| Mechanical : | Closed system or local exhaust to prevent generation and inhalation of dust. |
| Special : | N/A |
| Other : | N/A |
| Eye protection : | Safety glasses with side shields |
| Protection gloves : | Impervious to dust |
| Other protection accessories or clothing : | Emergency eyewash. Keep street and wok clothes separate. |

SECTION 10 : Fire and explosion hazards

| Flash Point | Explosive inferior limit (%) | Explosive superior limit (%) |
|---|------------------------------|------------------------------|
| Non-explosive | Non-explosive | Non-explosive |
| Extinguishing Media : | | |
| N/A | | |
| Special conditions that may cause fire or explosions : | | |
| Non-explosive / Non-Flammable | | |
| Special fire fighting procedures : | | |
| Wear standard fire fighting gear with self-contained breathing apparatus. | | |

This MSDS sheet is valid for a period of three (3) years following the date inscribed bellow

MSDS sheet prepared by : Christian Houle

Date : 01/ 01/ 2010

La Margna Inc considers that all the information contained in this msds sheet is accurate. We do not offer however, any warranty regarding the exactitude of this data or upon the results to be obtained from using the product. La Margna Inc. assumes no responsibility regarding personal injuries or property damage to vendees, users or third parties caused by the material. The vendor or users assume all risks associated with the use of any product sold by La Margna Inc.