

POLYKLEEN OXY

CLEANER FOR EPOXY GROUT



DESCRIPTION

POLYKLEEN OXY epoxy cleaner is a water-based biodegradable cleaner specifically formulated to remove epoxy film or leftover grout residue for a perfect clean. POLYKLEEN OXY can also be used to remove carpet adhesive. Its gel consistency facilitates vertical use.

CHARACTERISTICS

- pH: 6
- Formulated to remove epoxy residue after installation
- Non-toxic
- VOC content: 0 g/L
- Will not affect cement, plywood, ceramic, stone or vinyl composite
- Low odor

FORMATS

- 250 ml kit, including a scuff pad – 12 per box
- 1L bottle – 12 per box

TECHNICAL DATA AT 22°C

COVERAGE

depends on type of cleaning to be done. 1 liter can cover up to 10 m².

SHELF LIFE

24 months following production date. Must be stored in a dry and heated area.

TECHNICAL NOTES

For prolonged use, gloves are recommended.

MAIN USES

For residential and light commercial use, indoor and outdoor. Can be used over ceramic, porcelain, natural stone, polished quartz and cement. If used over composite stone/marble, do not let the product react for too long on the stone (maximum 3 hours). It will not affect cement or plywood but could affect stainless.

INSTRUCTIONS

APPLICATION



First, test on a small area to assure suitability of coverings. Spread a generous and uniform coat of remover using a paint brush. Every 10 minutes, scrub the surface with a white scrubbing pad to maximize the penetration of the remover for a period of 30 to 60 minutes. Avoid letting the solution dry on the surface to be cleaned. Once the paint or grout residues are loosened up, scrub the surface with soapy water. Remove the cleaning solution with a liquid vacuum cleaner or a dry cloth. Rinse again and let it dry. Repeat the application process if necessary.

LIMITATIONS

- Keep out of reach of children.
- Wear safety glasses and gloves when applying.
- Can be used on resin composite stone, quartz or resin, and marble - with care.
- Do not let the cleaner sit on composite stone for more than 3 hours.
- Acrylic surfaces must be protected.
- Avoid freezing.
- Test on a small surface to ensure suitability of covering.

WARRANTY

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. Ceraflex can help to achieve the following credits.

INDOOR ENVIRONMENTAL QUALITY:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
IEQ Credit 4.1 - Low Emitting Materials

MATERIALS AND RESOURCES:

MR Credit 5.1 - 10% extracted and manufactured regionally
MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

OTHER ENVIRONMENTAL DATA:

- Biodegradable
- In conformity with OCDE 301 E rule
- Meets Terra Choice / Écologo specifications
- Paint & varnish remover CCD: 1051

CAUTION



Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

HEALTH AND SAFETY

Refer to the MSDS on our website for handling recommendations.

TECHNICAL SUPPORT

For questions, please contact our customer service PROFIX toll free:
1-800-463-6850 or info@profixsystems.com.

PROFIX is a registered trademark.

LA MARGNA INC.
412, Saint-Sacrement, Quebec (Quebec) G1N 3Y3 CANADA
T (418) 688-8286
F (418) 688-2070
www.profixsystems.com

LIABILITY

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications. • April 1, 2012