

9022

LATEX ADDITIVE



DESCRIPTION

LATEX 9022 is a polymer latex-based liquid used to improve adhesion, flexibility, and freeze/thaw resistance. Ideal for exterior installations. LATEX 9022 replaces the water normally used in grout. Mix with POLY 500 polymer grouts for exterior use. LATEX 9022 will darken the colour of grout.

LATEX 9022 greatly increases adhesion between the existing concrete and the top layer, while also increasing flexibility and improving the grout's resistance to variations in temperature.

CHARACTERISTICS

- Increases flexibility, thereby improving resistance to variations in temperature
- Improves grout's shock resistance
- Polymer-fortified
- For indoor and outdoor use

FORMATS

- 1 L container – 12 per box
- 4 L container – 4 per box

TECHNICAL DATA AT 22°C

ONCE MIXED WITH GROUT

Force de compression	3000 psi
Absorption d'eau	Moins de 4 %
Densité	120 lbs / po
Niveau de COV	0 g/L

SHELF LIFE

24 months following production date. Must be stored in a dry and heated area.

TECHNICAL NOTES


LATEX 9022 replaces the water normally used in preparing grout. The same proportions are generally used. See the grout manufacturer's instructions.

INSTRUCTIONS

UNDERLAYMENT

The underlayment is the most important step for a long lasting result. Refer to the "Good supports" technical bulletin on our website. The underlayment must meet the TTMAC and the TCA standards.


MIX



Use pure latex latex 9022 for exterior applications (4 litres of LATEX 9022 mixed with 22.7 kg of POLY 500 sanded grout). For interior applications, dilute with clean water at a ratio of 1:1. Add the grout to the latex to obtain a smooth and thick consistency. Let sit for 10 minutes and stir again.


Ratio: Approximately 850 ml of latex 9022 per 4.5 kg of POLY 500.
(powder/water : 3 for 1)

APPLICATION



See POLY 500 technical sheet.

CLEANING



Promptly clean tools with water while material is fresh.

LIMITATIONS

- Do not freeze.
- Must be mixed with POLY 500 grout for outdoor use.

WARRANTY

This product is guaranteed for 1 year when used according to La Margna Inc., the TTMAC and the TCA instructions. An extension of this warranty is available. For more information, visit our website.

LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. 9022 can help to achieve the following credits.

INDOOR ENVIRONMENTAL QUALITY:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems

IEQ Credit 4.1 - Low Emitting Materials

IEQ Credit 4.3 - Low Emitting Materials - Flooring systems

MATERIALS AND RESOURCES:

MR Credit 5.1 - 10% extracted and manufactured regionally

MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

HEALTH AND SAFETY

Refer to the MSDS on our website for handling recommendations.

TECHNICAL SUPPORT

For questions, please contact our customer service PROFIX toll free:
1-800-463-6850 or info@profixsystems.com.

PROFIX is a registered trademark.

LA MARGNA INC.

412, Saint-Sacrement, Quebec (Quebec) G1N 3Y3 CANADA

T (418) 688-8286

F (418) 688-2070

www.profixsystems.com

LIABILITY

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications. • April 1, 2012