

POLY 300

CEMENT GROUT COLORANT



DESCRIPTION

POLY 300 is a colorant for cement grout joints. It can be applied over floor grout (POLY 500) and wall grout (POLY 600).

CHARACTERISTICS

- Available in PROFIX's 30 colours
- Easy to apply
- Water-based acrylic product

FORMAT

- 225 ml bottle – 12 per box

TECHNICAL DATA AT 22°C

COVERAGE

- A 225 ml tube covers approximately:
- 100 linear feet for joints 1/4"

N.B. These are rough measures. Coverage varies according to joint width, deepness and method of application.

SHELF LIFE

24 months following production date. Must be stored in a dry and heated area.

TECHNICAL NOTES

MAIN USE

- For indoor residential and commercial use. POLY 300 is specially formulated for colouring grout.
- Specially formulated for grout colouring. It can be used to refresh grout's original colour, modify the colour, or adjust the colour after installation.
- Because of the 2 different colour bases, some colour variations may occur between grout and dye.

INSTRUCTIONS

SUBSTRATE PREPARATION




Test on a small surface first to ensure suitability of coverings. Allow grout to dry for 14 days. To ensure that the colorant penetrates well, clean the surface thoroughly using POLYKLEEN CRETE grout cleaner: (not recommended for marble and limestone).

FOR PREVIOUSLY SEALED GROUT, USE THE PROPER PROFIX REMOVER:

- Water-based sealer: use NU ZONE W stripper
- Solvent-based sealer: use NU ZONE S stripper

APPLICATION



Shake well before using. First, test on a small surface to assure suitability of coverings. Spread uniformly over the grout by adjusting the pouring lip and by using a thin paintbrush. Applying 2 thin coats is generally sufficient. Let dry 2 to 3 hours between each coat. Wipe excess remaining on the tiles as soon as the joint is dry.

Properly aerate the area during drying and hardening time. Avoid rubbing the surface for 15 days.

POROUS TILES: Using a damp cloth, wipe excess off tiles as soon as the joints are dry.

NON-POROUS TILES AND GLAZED FINISH TILES: You can wait up to 24 hours to remove the surplus on the tiles using a damp cloth or a rough sponge.

RECOMMENDED HARDENING TIME: 7 days.

CLEANING

Use a neutral soap (pH 7-9), such as POLYKLEEN FLOR cleaner.

LIMITATIONS

- Keep out of reach of children
- Wear safety glasses and gloves when applying
- Avoid freezing

WARRANTY

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. Ceraflex can help to achieve the following credits.

INDOOR ENVIRONMENTAL QUALITY:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems

IEQ Credit 4.1 - Low Emitting Materials

MATERIALS AND RESOURCES:

MR Credit 5.1 - 10% extracted and manufactured regionally

MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

CAUTION



Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

HEALTH AND SAFETY

Refer to the MSDS on our website for handling recommendations.

TECHNICAL SUPPORT

For questions, please contact our customer service PROFIX toll free: 1-800-463-6850 or info@profixsystems.com.

PROFIX is a registered trademark.

LA MARGNA INC.

412, Saint-Sacrement, Quebec (Quebec) G1N 3Y3 CANADA

T (418) 688-8286

F (418) 688-2070

www.profixsystems.com

LIABILITY

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications. • April 1, 2012