

AQUA PEARL

WATER-BASED SEALER FOR DENSE TILES



DESCRIPTION

AQUA PEARL is a range of water-based sealers for porous surfaces such as marble, slate and natural stone. Sealers will slightly enhance natural colours and improve resistance to floor wear down, scratches and heel marks, as well as calcium, acid products and greasy substances.

CHARACTERISTICS

- Faint odour
- Dries quickly
- pH: 8.5
- Waterproof
- Enhances colour
- Water-based

FORMATS

- 1L bottle – 12 per box
- 4L bottle – 4 per box

TECHNICAL DATA AT 22°C

COVERAGE

1L covers approximately 250 ft² (varies depending on tile porosity).

SHELF LIFE

24 months following production date (stored in a dry and heated area).

TECHNICAL NOTES

MAIN USES

For residential or commercial use. Can be applied over floors, tables, marble walls, dense slate, natural stone, composite or terrazzo. It is suitable for natural finish tiles. For indoor use only.

INSTRUCTIONS

SUBSTRATE PREPARATION




Allow new cement grout to dry for 7 to 14 days. Clean the surface well to allow the sealer to penetrate well. Use POLYKLEEN CRETE tile cleaner (not recommended for marble and limestone).

PREVIOUSLY SEALED USE THE PROPER PROFIX REMOVER:


- Water-based sealer: use NU ZONE W stripper
- Solvent-based sealer: use NU ZONE S stripper

APPLICATION



Test first on a small surface to ensure suitability of covering. Spread delicately with a paint brush to avoid air bubbles formations. Do not use a sponge roller. The Application of 1 to 3 thin and uniform coats is usually sufficient. Wipe off excess sealant. The first coat must be completely dry before applying the second.

CLEANING



Use a neutral soap (pH 7-9) such as POLYKLEEN FLOR cleaner.

LIMITATIONS

- Avoid freezing
- Keep out of reach of children
- Wear safety glasses and gloves when applying
- For outdoor installations, the temperature must not drop below 10°C at the time of installation and for a period of 24 hours
- Do not use over polished tiles.

WARRANTY

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. Aqua Pearl can help to achieve the following credits.

INDOOR ENVIRONMENTAL QUALITY:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems

IEQ Credit 4.1 - Low Emitting Materials

IEQ Credit 4.3 - Low Emitting Materials - Flooring systems

MATERIALS AND RESOURCES:

MR Credit 5.1 - 10% extracted and manufactured regionally

MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

OTHER ENVIRONMENTAL DATA :

- Low VOC formula

- Biodegradable

- In conformity with OCDE 301 E rule

- Meets Terra Choice / Écologo specification

- Architectural surface sealer CCD: 047

CAUTION



In case of contact with eyes or skin, rinse thoroughly with water. If inhaled, get fresh air. If ingested, do not force vomiting but rather drink lots of water. If irritation persists, seek medical attention.

HEALTH AND SAFETY

Refer to the MSDS on our website for handling recommendations.

TECHNICAL SUPPORT

For questions, please contact our customer service PROFIX toll free:
1-800-463-6850 or info@profixsystems.com.

PROFIX is a registered trademark.

LA MARGNA INC.
412, Saint-Sacrement, Quebec (Quebec) G1N 3Y3 CANADA
T (418) 688-8286
F (418) 688-2070
www.profixsystems.com

LIABILITY

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications. • April 1, 2012