

AQUA XT

WATER-BASED SEALER FOR CEMENT GROUT



DESCRIPTION

AQUA XT is a thermoplastic water-based sealer for cement based grout. AQUA XT penetrates the surface to protect against calcium, acid products and greasy substances.

CHARACTERISTICS

- Slightly enhances colour
- Provides excellent protection
- pH : 8.5
- Dries quickly

FORMATS

- 250 ml bottle – 24 per box
- 500 ml bottle – 12 per box
- 1 L bottle – 12 per box

TECHNICAL DATA AT 22°C

COVERAGE

500 ml cover approximately 600 linear ft, approximately 300 ft² to 400 ft² area with 12"x 12" tiles and 1/4" joints.

Coverage varies according to width, surface porosity and texture, and method of application.

SHELF LIFE

24 months following production date. Must be stored in a dry and heated area.

TECHNICAL NOTES

DO NOT USE IN VERY HUMID AREAS OR ON FREQUENTLY WET SURFACES. In these cases, a solvent-based impregnator sealer such as MICROXPEL.

MAIN USE

For interior residential and commercial installations. Can be used over mortar or cement joints and on concrete floors.

INSTRUCTIONS

SUBSTRATE PREPARATION




Test on a small surface first to ensure suitability of covering. Allow grout to dry for 14 days. To ensure that the sealer penetrates well, clean the surface thoroughly using the POLYKLEEN CRETE cleaner for grout residues (not recommended for marble and limestone).

FOR PREVIOUSLY SEALED GROUT, USE THE PROPER PROFIX REMOVER:

- Water-based sealer: use Nu Zone W remover.
- Solvent-based sealer: use Nu Zone S remover.

APPLICATION



Test first on a small surface to assure suitability of covering. Pour over the joints and spread using a narrow paint brush. Allow to dry 30 minutes between each coat or until surface is completely dry. Two thin coats are sufficient for most surfaces. Remove excess on the sides of the tiles using a humid cloth. Surface is ready for circulation 2 to 3 hours after application. Hardening time: 3 days.

CLEANING



Use a neutral soap (PH : 7-9), such as POLYKLEEN FLOR floor cleaner.

LIMITATIONS

- Keep out of reach of children
- Wear safety glasses and gloves when applying
- Avoid freezing
- For outdoor installations, the temperature must not drop below 10°C at the time of installation and for a period of 24 hours

WARRANTY

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. AQUA XT can help to achieve the following credits.

INDOOR ENVIRONMENTAL QUALITY:

- IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
- IEQ Credit 4.1 - Low Emitting Materials
- IEQ Credit 4.3 - Low Emitting Materials - Flooring systems

MATERIALS AND RESOURCES:

- MR Credit 5.1 - 10% extracted and manufactured regionally
- MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

OTHER ENVIRONMENTAL DATA:

- Low VOC formula
- Biodegradable
- In conformity with OCDE 301 E rule
- Meets Terra Choice / Écologo specifications
- Architectural surface sealer CCD: 047

CAUTION



Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

HEALTH AND SAFETY

Refer to the MSDS on our website for handling recommendations.

TECHNICAL SUPPORT

For questions, please contact our customer service PROFIX toll free: 1-800-463-6850 or info@profixsystems.com.

PROFIX is a registered trademark.

LA MARGNA INC.

412, Saint-Sacrement, Quebec (Quebec) G1N 3Y3 CANADA

T (418) 688-8286

F (418) 688-2070

www.profixsystems.com

LIABILITY

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications. • April 1, 2012