

STONE HD

SOLVENT-BASED SEALER FOR TILES

PROFIX
TILE AND STONE INSTALLATION SYSTEMS



DESCRIPTION

STONE HD is a range of solvent-based sealers (mineral essence that releases a mild odour) for porous surfaces. Sealers enhance natural colour and leave a glossy finish. They are highly resistant to water, grease and oil.

CHARACTERISTICS

- Enhances natural colors
- Excellent surface coating for MICROXPEL

FORMATS

- STONE HD - glossy
- 500 ml bottle - 12 per box
- 1 L bottle - 12 per box
- 4 L bottles - 4 per box

TECHNICAL DATA AT 22°C

COVERAGE

- 500 ml covers approximately 75 to 100 ft²
- 1L covers approximately 150 to 200 ft²
- 4 L covers approximately 700 to 800 ft²

SHELF LIFE

24 months following production date. It must be stored in a dry and heated area.

TECHNICAL NOTES

For prolonged use, gloves are recommended.

MAIN USE

For residential or commercial use, indoors and outdoors. Ideal for sealing Mexican tiles, concrete and cement, porous Chinese slate, granite and textured marble, quartz-resin and marble-resin composite stone, mortar joints, cement grout and sandstone.

INSTRUCTIONS

SUBSTRATE PREPARATION




Natural stone must be sealed before installing the grout. Allow new cement grout to dry for 7 days before sealing it. Clean the surface thoroughly to ensure good penetration of the sealant. Use cleaner POLYKLEEN FLOR or NU ZONE W.

FOR PREVIOUSLY SEALED GROUT, USE THE PROPER PROFIX REMOVER:


- Water-based sealer: use NU ZONE W stripper
- Solvent-based sealer: use NU ZONE S stripper

APPLICATION



Test first on a small surface to ensure suitability of covering. Spread delicately with a paint brush to avoid air bubbles formations. Do not use a sponge roller. The Application of 1 to 2 thin and uniform coats is usually sufficient. Wipe off excess sealant. The first coat must be completely dry before applying the second.

CLEANING



Routine cleaning: use a neutral soap (pH: 7 - 9) such as POLYKLEEN FLOR.

LIMITATIONS

- Keep out of reach of children
- Wear safety glasses rubber gloves
- Inflammable liquid: mineral spirit
- For outdoor installations, the temperature must not fall below 10°C during the installation and for a period of 24 hours after the installation.

WARRANTY

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. Ceraflex can help to achieve the following credits.

INDOOR ENVIRONMENTAL QUALITY:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
IEQ Credit 4.1 - Low Emitting Materials

MATERIALS AND RESOURCES:

MR Credit 5.1 - 10% extracted and manufactured regionally
MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

OTHER ENVIRONMENTAL DATA:

- VOC: 80 gr / 100 ml

CAUTION



Flammable product, contains mineral spirits. Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses and a breathing mask with filters against organic vapors is recommended during interior applications. Before proceeding test first on a small non visible area to assure safe use, suitability results.

HEALTH AND SAFETY

Refer to the MSDS on our website for handling recommendations.

TECHNICAL SUPPORT

For questions, please contact our customer service PROFIX toll free: 1-800-463-6850 or info@profixsystems.com.

PROFIX is a registered trademark.

LA MARGNA INC.

412, Saint-Sacrement, Quebec (Quebec) G1N 3Y3 CANADA

T (418) 688-8286

F (418) 688-2070

www.profixsystems.com

LIABILITY

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications. • April 1, 2012