

9022

LATEX ADDITIVE

PROFIX



Description

LATEX 9022 is a polymer latex-based liquid used to improve adhesion, as well as shock, chemical, and freeze/thaw resistance. LATEX 9022 replaces the water normally used in grout. Mix with POLY 500/600 polymer grouts for exterior use. LATEX 9022 will darken the colour of grout.

LATEX 9022 greatly increases adhesion between the existing concrete and the top layer, while also increasing flexibility and improving the grout's resistance to variations in temperature.

Characteristics

- Increases flexibility, thereby improving resistance to variations in temperature
- Improves grout's shock resistance
- Polymer-fortified
- For indoor and outdoor use

Formats

- 1 L container – 12 per box
- 4 L container – 4 per box



Technical data @ 22°C

Once mixed with grout

Compression force	3000 psi
Water absorption	Less than 4%
Density	120 lbs / in
VOC level	0 g/L

Shelf life

LATEX 9022: 24 months following production date. Must be stored in a dry and heated area.

Technical notes

LATEX 9022 replaces the water normally used in preparing grout. The same proportions are generally used. See the grout manufacturer's instructions.


Instructions

Underlayment

The underlayment is the most important step for a long lasting result. Refer to the "Good supports" technical bulletin on our website. The underlayment must meet the TTMAC and the TCA standards.

Mix

As a grout additive:



Use pure LATEX 9022 for exterior applications (4 litres of LATEX 9022 mixed with 22.7 kg of POLY 500 sanded grout). For interior applications, dilute with clean water at a ratio of 1:1. Add the grout to the latex to obtain a smooth and thick consistency. Let sit for 10 minutes and stir again.



9022
Latex additive

Tile and Stone Installation Systems

Application



See POLY 500/600 technical sheet

Cleaning



Promptly clean tools with water while material is fresh.

Indoor Environmental Quality:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

MR Credit 5.1 - 10% extracted and manufactured regionally
MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

Health and Safety

Refer to the MSDS on our website for handling recommendations.

Limitations

- Do not freeze
- Must be mixed with POLY 500 grout for outdoor use

Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at : info@profixsystems.com

PROFIX is a registered trademark.

Warranty

This product is guaranteed for 1 year when used according to La Margna Inc., the TTMAC and the TCA instructions. An extension of this warranty is available. For more information, visit our website.

La Margna Inc.
412, St-Sacrement Québec, Québec
G1N 3Y3 CANADA
Tel.: (418) 688-8286
Fax: (418) 688-2070

www.profixsystems.com

LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. 9022 can help to achieve the following credits:

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010