

# AQUA XT

## WATER-BASED SEALER FOR CEMENT GROUT

# PROFIX



### Description

AQUA XT is a thermoplastic water-based sealer for cement grout that does not enhance colour. AQUA XT penetrates the surface to protect against calcium, acid products and greasy substances.

#### Characteristics

- Slightly enhances colour
- Provides excellent protection
- pH : 8.5
- Dries quickly

#### Formats

- 250 ml bottle – 24 per box
- 500 ml bottle – 12 per box
- 1L bottle – 12 per box

### Technical data @ 22°C

#### Coverage:

- 500 ml cover approximately 600 linear ft, corresponding approximately to a 300 ft<sup>2</sup> to 400 ft<sup>2</sup> area with 12"x 12" tiles and 1/4" joints.

Coverage varies according to width, surface porosity and texture, and method of application.

#### Shelf life

AQUA XT: 24 months following production date (stored in a dry and heated area).

### Technical notes

DO NOT USE IN VERY HUMID AREAS OR ON FREQUENTLY WET SURFACES. In these cases, a solvent-based sealer such as SCELLIX 18%, or porous surface sealers, such as STONE HD (natural, silky or glossy), are recommended.

#### Main use

For residential and commercial uses. Can be used over mortar or cement joints and on concrete floors.

### Instructions

#### Substrate preparation




Test on a small surface first to ensure suitability of coverings. Allow grout to dry for 14 days. To ensure that the sealer penetrates well, clean the surface thoroughly using the PROFIX POLYKLEEN CRETE cleaner for grout residues (not recommended for marble and limestone).

For previously sealed grout, use the proper PROFIX remover:

- Water-based sealer: use NU ZONE W stripper
- Solvent-based sealer: use NU ZONE S stripper

#### Application


Pour over joints and spread using a small paint brush. Allow to dry 30 minutes between each coat or until surface is completely dry. Two thin coats are usually enough for most surfaces. Once joints are dry (30 minutes), wipe excess off tiles using a damp cloth.



Surface is ready for circulation 2 to 3 hours after applying. Recommended hardening time is 3 days.

#### Cleaning

Use a neutral soap (PH : 7-9), such as PROFIX POLYKLEEN FLOR floor cleaner.



### Limitations

- Keep out of reach of children
- Wear safety glasses and gloves when applying
- Avoid freezing
- For outdoor installations, the temperature must not drop below 10°C at the time of installation and for a period of 24 hours

# PROFIX

Tile and Stone Installation Systems

# AQUA XT

Water-based sealer for cement grout

## Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

## Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. AQUA XT can help to achieve the following credits:

Indoor Environmental Quality:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems  
IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

MR Credit 5.1 - 10% extracted and manufactured regionally  
MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

Other environmental data:

- Low VOC formula
- Biodegradable
- In conformity with OCDE 301 E rule
- Meets Terra Choice / Écologo specifications
- Architectural surface sealer CCD: 047

## Caution

Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010

## Health and Safety



Refer to the MSDS on our website for handling recommendations.

## Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: [info@profixsystems.com](mailto:info@profixsystems.com)

PROFIX is a registered trademark.

La Margna Inc.  
412, St-Sacrement Québec, Québec  
G1N 3Y3 CANADA  
Tel.: (418) 688-8286  
Fax: (418) 688-2070

[www.profixsystems.com](http://www.profixsystems.com)