

AQUAXPEL

WATER-BASED PENETRATING SEALER

PROFIX



Description

AQUAXPEL is a water-based sealer formulated to protect natural and quartz composite stone surfaces, ceramic and porcelain tiles. It can be applied on floors, walls, counters and backsplashes and provides water and oil repellent protection.

Characteristics

- Faint odor
- pH : 7.85
- Color : white translucent
- Low color enhancement
- Waterproof
- Dries without leaving a film on surface

Formats

1L bottle – 12 per box

Technical data @ 22°C

Coverage

1 liter covers approximately 25m² or 250ft² (varies with the porosity and the texture of the surface).

Shelf life

AQUAXPEL : 24 months following production date (stored in a dry and heated area)

Technical notes

For prolonged use, gloves are recommended.

Main use

For residential and commercial use, both indoors and outdoors.

Instructions

Substrate preparation

Surface must be dry, thoroughly clean, sound, and free of all foreign matter including previous sealers and mortar retardants. Test on a small surface first to ensure suitability of coverings. Wait 7 to 14 days (or as per manufacturer's recommendation) to allow proper curing of new grout before applying sealer. To ensure deep cleaning of the surface use PROFIX POLYKLEEN CRETE cleaner (not recommended for marble and calcareous stones).

Application



Apply one thin coat evenly with a sponge, a paint brush or a paint roller. Wait 20 to 30 minutes to allow the sealer to penetrate the surface. Apply a second coat while the surface is still damp and wait 20 to 30 minutes to allow the sealer to penetrate the surface. Wipe off excess sealer with a dry cloth or a paper towel.

If applied on a vertical surface, make sure that there is no sealer accumulation in the joints on top of the tiles to avoid the formation of streaks during the drying period.

Drying

Sealer will be dry on surface after 1-3 hours and it will completely harden after 36-72 hours. Wait for 72 hours before allowing normal circulation.

Cleaning

Use a neutral soap (pH 7-9), such as PROFIX POLYKLEEN FLOR floor cleaner.

Limitations

- Keep out of reach of children
- Keep at room temperature in a dry area
- Avoid from freezing
- For outdoor installations, the temperature must not drop below 10°C at the time of installation and for a period of 24 hours



AQUAXPEL
Water-based penetrating sealer

Tile and Stone Installation Systems

Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. AQUAXPEL can help to achieve the following credits:

Indoor Environmental Quality:

- IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
- IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

- MR Credit 5.1 - 10% extracted and manufactured regionally
- MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

Other environmental data:

- VOC: 10 gr/100ml

Caution



Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

Health and Safety

Refer to the MSDS on our website for handling recommendations.

Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: info@profixsystems.com

PROFIX is a registered trademark.

La Margna Inc.
412, St-Sacrement Québec, Québec
G1N 3Y3 CANADA
Tel.: (418) 688-8286
Fax: (418) 688-2070

www.profixsystems.com

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010