

# AQUA PEARL

## WATER-BASED SEALER FOR DENSE TILES



# PROFIX



### Description

Three choices of water-based sealers with various finishes.

- Dense surface sealer – glossy (acrylic finish)
- Dense surface sealer – silk (acrylic finish)
- Dense surface sealer – natural (acrylic finish)

Aqua Pearl is a range of water-based sealers for porous or polished surfaces such as marble, slate and natural stone. Sealers will slightly enhance natural colours and improve resistance to floor wear down, scratches and heel marks, as well as calcium, acid products and greasy substances.

#### Characteristics

- Faint odour
- Dries quickly
- pH: 8.5
- Non-flammable
- Enhances colour
- Water-based

#### Formats

- 1L bottle – 12 per box
- 4L bottle – 4 per box

### Technical data @ 22°C

Coverage: 1L covers approximately 250 ft<sup>2</sup> (varies depending on tile porosity).

#### Shelf life

Aqua Pearl: 24 months following production date (stored in a dry and heated area).

### Technical notes

For prolonged use, gloves are recommended.

#### Main uses

For residential or commercial use. Can be applied over floors, tables, marble walls, dense slate, natural stone, composite or terrazzo. It is suitable for soft-ened, polished or natural finish tiles. For indoor use only.

### Instructions

#### Substrate preparation

Test on a small surface first to ensure suitability of coverings.




Allow new cement grout to dry for 7 to 14 days. Clean the surface well to allow the sealer to penetrate well. Use PROFIX POLYKLEEN CRETE tile cleaner (not recommended for marble and limestone).

#### Previously sealed

Use the proper PROFIX remover:

- Water-based sealer: use NU ZONE W stripper
- Solvent-based sealer: use NU ZONE S stripper

#### Application



Spread with a polishing ramble, a sponge or a sheepskin applicator. Two or three overlapping thin coats are sufficient for most surfaces. Allow to dry 30 to 45 minutes between each application.

**DO NOT USE A CLOTH TO APPLY THE FINISH BECAUSE A WHITE FILM COULD FORM OVER THE SURFACE AFTER DRYING.**

Glossy finish option: polishing is not required but increases durability when done at high speed. Sweep surface and rinse with clean water between coats. Let air dry.

## Tile and Stone Installation Systems

Surface is ready for circulation 2 to 3 hours after applying. Proceed the same way for all coats.

### Cleaning

Use a neutral soap (pH 7-9) such as PROFIX POLYKLEEN FLOR cleaner.

### Limitations

- Avoid freezing
- Keep out of reach of children
- Wear safety glasses and gloves when applying
- For outdoor installations, the temperature must not drop below 10°C at the time of installation and for a period of 24 hours

### Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

### Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. AQUA PEARL can help to achieve the following credits:

Indoor Environmental Quality:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems  
IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

MR Credit 5.1 - 10% extracted and manufactured regionally  
MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

### Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010

Other environmental data :

- Low VOC formula
- Biodegradable
- In conformity with OCDE 301 E rule
- Meets Terra Choice / Écologo specification
- Architectural surface sealer CCD: 047

### Caution



In case of contact with eyes or skin, rinse thoroughly with water. If inhaled, get fresh air. If ingested, do not force vomiting but rather drink lots of water. If irritation persists, seek medical attention.

### Health and Safety

Refer to the MSDS on our website for handling recommendations.

### Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: [info@profixsystems.com](mailto:info@profixsystems.com)

PROFIX is a registered trademark.

La Margna Inc.  
412, St-Sacrement Québec, Québec  
G1N 3Y3 CANADA  
Tel.: (418) 688-8286  
Fax: (418) 688-2070

[www.profixsystems.com](http://www.profixsystems.com)