

MICROXPEL

IMPREGNATOR SEALER

PROFIX



Description

MICROXPEL is a solvent-based impregnator sealer that penetrates surfaces and fills pores without leaving a film on surface. MICROXPEL's microscopic molecular formula enhances the colour of tiles and leaves a natural finish. It is water and oil resistant.

Characteristics

- Mild odour
- Silicone-free and will not yellow your tiles
- Enhances natural colours
- Excellent undercoating

Format

500 ml bottle - 12 per box
1L bottle - 12 per box
4L bottle - 4 per box

Technical data @ 22°C

Coverage: 1L covers approximately 150-200 ft² (varies depending on tile porosity)

Shelf life

MICROXPEL: 24 months following production date (stored in a dry and heated area)

Technical notes

For prolonged use, gloves are recommended.

Main uses

For residential or commercial use, indoors and outdoors. Can be applied over floors, on walls and showers, and over tables made of granite, marble, low porous slate, natural stone or composite. MICROXPEL can also be used on polished surfaces and is often used as an undercoating before using STONE HD sealer.

Instructions

Substrate preparation


Test on a small surface first to ensure suitability of coverings.

Allow new cement grout to dry for 7 to 14 days. Clean the surface properly to allow a good penetration of the sealer. Use PROFIX POLYKLEEN CRETE cleaner for grout residues (not recommended for marble and limestone).

For previously sealed grout, use the proper PROFIX remover:

- Water-based sealer: use NU ZONE W stripper
- Solvent-based sealer: use NU ZONE S stripper


Application



Spread using a polishing ramble, a sponge or a sheepskin applicator. Two thin coats are sufficient for most surfaces. Allow to dry for 60 to 90 minutes between each application.

Normal circulation can resume 12 hours after the last coat has dried.

Cleaning



Use a neutral soap (pH 7-9) such as PROFIX POLYKLEEN FLOR floor cleaner.



MICROXPEL

Impregnator sealer

Tile and Stone Installation Systems

Limitations

- Keep out of reach of children
- Wear safety glasses and gloves when applying
- Flammable liquid: mineral spirits
- For outdoor installations, the temperature must not drop below 10°C at the time of installation and for a period of 24 hours

Caution



Flammable product, contains mineral spirits. Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses and a breathing mask with filters against organic vapors is recommended during interior applications.

Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

Health and Safety

Refer to the MSDS on our website for handling recommendations.

Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. MICROXPEL can help to achieve the following credits:

Indoor Environmental Quality:

- IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
- IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

- MR Credit 5.1 - 10% extracted and manufactured regionally
- MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

Other environmental data:

- VOC: 90gr / 100ml

Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: info@profixsystems.com

PROFIX is a registered trademark.

La Margna Inc.
412, St-Sacrement Québec, Québec
G1N 3Y3 CANADA
Tel.: (418) 688-8286
Fax: (418) 688-2070

www.profixsystems.com

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010