

POLY 300

GROUT COLORANT

PROFIX



Description

Grout colouring for cement joints. Can be applied over floor grout (POLY 500) and wall grout (POLY 600).

Characteristics

- Available in PROFIX's 30 colours
- Easy to apply

Format

1L bottle – 12 per box

Technical data @ 22 C

Coverage: 250 ml covers approximately 100 linear meters (300 feet), corresponding to an area approximately 100 feet square covered with 12" x 12" tiles. Coverage varies according to width and grout porosity.

Shelf life

POLY 300: 24 months following production date (stored in a dry and heated area).

Technical notes

- Gloves are recommended when using for an extended period of time.
- Because of the 2 different colour bases, some colour variations may occur between grout and dye.

Main use

For residential and commercial use. POLY 300 is specially formulated for colouring grout. It can be used to refresh grout's original colour, modify the colour, or adjust the colour after installation.

Instructions

Substrate preparation



Test on a small surface first to ensure suitability of coverings. Allow grout to dry for 14 days. To ensure the sealer penetrates well, clean the surface thoroughly using PROFIX Tile Cleaner PolyKleen Crete (not recommended for marble and limestone).

For grout that was previously sealed
Use PROFIX sealer removers:

- Water-based sealer: Use Nu Zone W stripper
- Solvent-based sealer: Use Nu Zone S stripper

Application

Shake well before using. Safety glasses and gloves are recommended when applying. Spread POLY 300 uniformly over the grout by adjusting the spout and using a thin paintbrush. Let dry 2 to 3 hours between each coat. The application of 2 thin coats is generally sufficient.

Properly aerate the area during drying and hardening time. Avoid rubbing the surface for 15 days.

Porous tiles: Using a damp cloth, wipe excess off tiles as soon as joints are dry.

Non-porous tiles and glazed finish tiles: You can wait up to 24 hours to remove the surplus on the tiles using a damp cloth or a rough sponge.

Recommended hardening time is 7 days.

Cleaning

Use a neutral soap (pH 7-9), such as PROFIX PolyKleen Flor floor cleaner.

Limitations

- Keep out of reach of children
- Wear safety glasses and gloves when applying
- Avoid freezing

Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an independent examination of the documentation submitted by the design and construction teams. POLY 300 can help to achieve the following credits:

Indoor Environmental Quality:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems

IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

MR Credit 5.1 - 10% extracted and manufactured regionally

MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for certified letters.

Caution



In case of contact with eyes or skin, rinse thoroughly with water. If inhaled, get fresh air. If ingested, do not force vomiting, but rather drink lots of water. If irritation persists, seek medical attention.

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

January 12th, 2010

Health and Safety

Refer to the MSDS on our website for handling recommendations.

Questions? Call the PROFIX customer care team toll-free at: 1-800-838-4237, or e-mail us at: info@profixsystems.com

PROFIX is a registered and manufactured trademark.

La Margna Inc.
412, St-Sacrement Québec, Québec
G1N 3Y3 CANADA
Tel.: (418) 688-8286
Toll-free: 1(800) 838-4237
Fax: (418) 688-2070
www.profixsystems.com