

# POLY 300

## CEMENT GROUT COLORANT

# PROFIX



### Description

POLY 300 is a colorant for cement grout joints. It can be applied over floor grout (POLY 500) and wall grout (POLY 600).

#### Characteristics

- Available in PROFIX's 30 colours
- Easy to apply
- Water-based acrylic product

#### Format

225 ml bottle – 12 per box

### Technical data @ 22°C

Coverage: 225 ml cover approximately 100 linear meters (300 feet), corresponding approximately to a 100 ft<sup>2</sup> area covered with 12" x 12" tiles. Coverage varies according to width and grout porosity.

#### Shelf life

POLY 300: 24 months following production date (stored in a dry and heated area).

### Technical notes

- Gloves are recommended for a prolonged use.
- Because of the 2 different colour bases, some colour variations may occur between grout and dye.

#### Main use

For indoor residential and commercial use. POLY 300 is specially formulated for colouring grout. It can be used to refresh grout's original colour, modify the colour, or adjust the colour after installation.

### Instructions

#### Substrate preparation




Test on a small surface first to ensure suitability of coverings. Allow grout to dry for 14 days. To ensure that the colorant penetrates well, clean the surface thoroughly using PROFIX POLYKLEEN CRETE grout cleaner: (not recommended for marble and limestone).

For previously sealed grout, use the proper PROFIX remover:

- Water-based sealer: use NU ZONE W stripper
- Solvent-based sealer: use NU ZONE S stripper

#### Application



Shake well before using. Safety glasses and gloves are recommended when applying. Spread POLY 300 uniformly over the grout by adjusting the spout and using a thin paintbrush. Let dry 2 to 3 hours between each coat. The application of 2 thin coats is generally sufficient.

Properly aerate the area during drying and hardening time.

Avoid rubbing the surface for 15 days.

Porous tiles: using a damp cloth, wipe excess off tiles as soon as the joints are dry.

Non-porous tiles and glazed finish tiles: you can wait up to 24 hours to remove the surplus on the tiles using a damp cloth or a rough sponge.

Recommended hardening time is 7 days.

#### Cleaning

Use a neutral soap (pH 7-9), such as PROFIX POLYKLEEN FLOR cleaner.

## Tile and Stone Installation Systems

### Limitations

- Keep out of reach of children
- Wear safety glasses and gloves when applying
- Avoid freezing

### Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

### Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. POLY 300 can help to achieve the following credits:

#### Indoor Environmental Quality:

- IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
- IEQ Credit 4.1 - Low Emitting Materials

#### Materials and Resources:

- MR Credit 5.1 - 10% extracted and manufactured regionally
- MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

#### Other environmental data:

- Low VOC formula
- Biodegradable
- In conformity with OCDE 301 E rule

#### Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010

### Caution



Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

### Health and Safety

Refer to the MSDS on our website for handling recommendations.

### Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: [info@profixsystems.com](mailto:info@profixsystems.com)

PROFIX is a registered trademark.

La Margna Inc.  
412, St-Sacrement Québec, Québec  
G1N 3Y3 CANADA  
Tel.: (418) 688-8286  
Fax: (418) 688-2070

[www.profixsystems.com](http://www.profixsystems.com)