

# POLY 400 U

## UNSANDED CAULKING

# PROFIX



### Description

PROFIX POLY 400 U is a 100% silicone formula unsanded caulking for bathrooms and kitchens. POLY 400 U dries into a thick and rubbery paste that resists humidity, moisture and vibration. Due to its consistency, it can easily be applied to ceilings and walls with no danger of leaking or subsidence.

#### Characteristics

- 100% silicone
- Moisture & mildew resistant
- Available in translucent and white

#### Format

310 ml tube – 10 per box

### Technical data @ 22°C

Initial set: 48 hours

Final set: 3-5 days (1/8" thickness; 50% relative humidity)

POLY 400 U meets or exceeds standard norms: ASTM C834

#### Coverage

A 310ml tube covers 100 linear ft for 1/8" x 1/8" joints and 25 linear ft for 1/4" x 1/4" joints.

N.B. These measures are approximate. Coverage varies according to joint width, deepness and method of application.

#### Shelf life

POLY 400 U: 24 months following production date (stored in a dry and heated area). This product may expand and overflow its container when frozen but the quality is not affected and can be used after being thawed.

### Technical notes

POLY 400 U will not bond to copper, magnesium, zinc, or other galvanised metals.

For residential or commercial use. Indoors and outdoors. Mainly used in bathtubs and showers, as well as for bathroom and kitchen sinks. POLY 400 U is ready to use.


### Instructions

#### Substrate preparation



Test a small surface first to ensure suitability of coverings.

#### Application



All backing surfaces must be dry, structurally sound, and free of any product (wax, sealant) that may act as bond barriers (in compliance with the TTMAC and the TCA industry standards). Rubber surfaces must be sanded and rinsed with acetone before application.

POLY 400 U is ready to use. A spatula or a piece of wood can be used to tool the surface. The sealant should be fully cured before coming in contact with water.

#### Cleaning



Excess caulking that has not yet dried can be removed with solvents.

## Curing



A vinegar smell is released during curing time.

## Limitations

- Keep out of reach of children
- Wear gloves during application
- Use in a well-ventilated area

## Warranty

This product is guaranteed for 1 year when used according to La Margna Inc., the TTMAC and the TCA instructions. An extension of this warranty is available. For more information, visit our website.

## LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. POLY 400 U can help to achieve the following credits:

Indoor Environmental Quality:

- IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
- IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

- MR Credit 5.1 - 10% extracted and manufactured regionally
- MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010

## Caution

Refer to the MSDS on our website for handling recommendations.

## Health and Safety



In case of contact with eyes or skin, rinse thoroughly with water. If inhaled, get fresh air. Seek medical attention.

## Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: [info@profixsystems.com](mailto:info@profixsystems.com)

PROFIX is a registered trademark.

La Margna Inc.  
412, St-Sacrement Québec, Québec  
G1N 3Y3 CANADA  
Tel.: (418) 688-8286  
Fax: (418) 688-2070

[www.profixsystems.com](http://www.profixsystems.com)