

# POLYKLEEN 9006

## ACID-BASED CLEANER FOR JOINTS



### Description

POLYKLEEN 9006 is a concentrated phosphoric acid-based cleaner for grout joints and cement. It removes grease, oil, mould, dirt and old grout stains, and can be used on a variety of tiles.

#### Characteristics

- Restores appearance of PROFIX grout joints
- Excellent grease cleaner
- Removes efflorescence (white powdery deposit on joints)
- pH: 1.2

#### Formats

- 500 ml bottle – 12 per box
- 1 L bottle – 12 per box

### Technical data @ 22°C

Coverage: depends on type of cleaning to be done.

Usage frequency: Subject to the frequency of cleaning and the types of products used.

#### Shelf life

POLYKLEEN 9006: 24 months following production date (stored in a dry and heated area).

### Technical notes

- It is very important to dilute this product with water; otherwise it could burn the cement and the grout joint.
- Standard cleaning: 50% 9006 / 50% water.
- Maximum concentration for cement: 70% 9006 / 30% water.

#### Usage

Test on a small surface first to ensure the product's suitability.

- Ceramic tiles
- Grout



- Brick
- Concrete
- Mosaic tiles




### Instructions

#### Substrate preparation



Ensure that the surface is suitable for cleaning with an acid-based cleaner. As the product has a strong odour, you must plan a good ventilation.

#### Application



Wear protective glasses and gloves during application. Avoid contact with skin. Use in a well-ventilated area.

#### Cleaning



Once cleaning is complete, rinse the entire surface thoroughly with water.

### Limitations

- Do not use on marble or limestone
- Might remove tile sealer

# PROFIX

# POLYKLEEN 9006

Acid-based cleaner for joints

Tile and Stone Installation Systems

## Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

## Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. POLYKLEEN 9006 can help to achieve the following credits:

Indoor Environmental Quality:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems  
IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

MR Credit 5.1 - 10% extracted and manufactured regionally  
MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

Other environmental data:

- Low VOC formula
- Biodegradable
- In conformity with OCDE 301 E rule
- Meets Terra Choice / Écologo specifications
- Bathroom cleaner CCD: 146J

## Caution



Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010

## Health and Safety

Refer to the MSDS on our website for handling recommendations.

## Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: [info@profixsystems.com](mailto:info@profixsystems.com)

PROFIX is a registered trademark.

La Margna Inc.  
412, St-Sacrement Québec, Québec  
G1N 3Y3 CANADA  
Tel.: (418) 688-8286  
Fax: (418) 688-2070

[www.profixsystems.com](http://www.profixsystems.com)