

POLYKLEEN GLUE

CARPET GLUE REMOVER



PROFIX



Description

POLYKLEEN GLUE removes acrylic and/or urethane based carpet glues, black glues, paints and pre-mixed cement grout residues. It is safe on concrete, ceramic and porcelain tiles, natural and quartz composite stones and VCT tiles. POLYKLEEN GLUE can be used on counters, floors and walls.

Characteristics

- Viscous formula for long lasting action
- pH (concentrated) : 6.5 - 7
- Color : clear transparent
- Slow evaporation for long term reaction
- Odor : Faint orange

Format

1L bottle – 12 per box

Technical data @ 22°C

Coverage : 1 liter covers approximately 50 ft² depending on the composition and thickness of the coats to be removed.

Shelf life

POLYKLEEN GLUE : 24 months following production date (stored in a dry and heated area).

Technical notes

For prolonged use, gloves are recommended.

Main use

For residential and commercial use, both indoors and outdoors.


Instructions

Substrate preparation



Test on a small surface first to ensure suitability of coverings.

Application



Spread a generous coat of remover all over the surface. Let the product work for 30 to 60 minutes, scrubbing the surface every 10 minutes with a black scuff pad or a hard bristle brush (recommended for textured surfaces).

Time required to soften material will vary with the chemical composition and the thickness of the coats of glue, paint or grout residues to be removed as well as the temperature and texture of the surface. Add warm water, scrub to remove all residues and remover and pick up, if possible, with a wet vacuum.

Cleaning

Rinse thoroughly with warm water or a diluted solution of PROFIX POLYKLEEN FLOR. Scrub the surface again with a hard brush to remove any remaining residues and wipe. Repeat if necessary. Allow to dry completely before applying a sealer, paint or another adhesive.

Limitations

- Keep out of reach of children.
- Protect baseboards made of varnished hardwood, plywood or MDF fiber. Cleaner could attack the glue in the baseboards and make them swell and could also remove partially the varnish on the baseboards.
- Wear safety glasses and gloves when applying.
- Do not use on marble or limestone.
- Can remove the sealer from your tiles.
- Avoid from freezing.

Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. POLYKLEEN GLUE can help to achieve the following credits :

Indoor Environmental Quality :

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources :

MR Credit 5.1 - 10% extracted and manufactured regionally
MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

Other environmental data :

- VOC : 75%
- Biodegradable
- In conformity with OCDE 301 E rule

Caution



May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010

Health and Safety

Refer to the MSDS on our website for handling recommendations.

Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: info@profixsystems.com

PROFIX is a registered trademark.

La Margna Inc.
412, St-Sacrement Québec, Québec
G1N 3Y3 CANADA
Tel.: (418) 688-8286
Fax: (418) 688-2070

www.profixsystems.com