

# POLYKLEEN OXY

## CLEANER FOR EPOXY GROUT



# PROFIX



### Description

PolyKleen Oxy epoxy cleaner is a water-based biodegradable cleaner specifically formulated to remove epoxy film or leftover grout residue for a perfect clean. PolyKleen Oxy can also be used to remove carpet adhesive. Its gel consistency facilitates vertical use.

#### Characteristics

- PH: 6
- Formulated to remove epoxy residue after installation
- Non-toxic
- VOC content: 0 g/L
- Will not affect cement, plywood, ceramic, stone or vinyl composite
- Low odor

#### Formats

250 ml set, including brush – 12 per box  
1L bottle – 12 per box

### Technical data @ 22°C

Coverage: depends on type of cleaning to be done.  
1 liter can cover up to 10 m<sup>2</sup> (ft<sup>2</sup>)

#### Shelf life

POLYKLEEN OXY: 24 months following production date (stored in a dry and heated area).

### Technical notes


For prolonged use, gloves are recommended.

#### Main uses

For residential and light commercial use, indoor and outdoor. Can be used over ceramic, porcelain, natural stone, polished quartz and cement. If used over composite stone/marble, do not let the product react for too long on the stone (maximum 3 hours). It will not affect cement or plywood but could affect stainless.

### Instructions

#### Application



Varies according to the quantity of grout to be cleaned.

Test on a small surface first to ensure suitability of coverings.

Apply generously using a paintbrush. Let the product act for 30 to 45 minutes. However, do not let POLYKLEEN OXY dry over the surface. Use the brush included or, if necessary, a small scraper (be gentle with your tiles). Rinse thoroughly using lots of water and make sure to remove any remaining POLYKLEEN OXY cleaner and epoxy residues.

To remove chunks of epoxy, let the product work for 7-9 hours.

### Limitations

- Keep out of reach of children.
- Wear safety glasses and gloves when applying.
- Can be used on resin composite stone, quartz or resin, and marble - with care
- Do not let the cleaner sit on composite stone for more than 3 hours
- Acrylic surfaces must be protected
- Avoid freezing
- Test on a small surface to ensure suitability of covering

### Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

# PROFIX

Tile and Stone Installation Systems

# POLYKLEEN OXY

Cleaner for epoxy grout

## Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. POLYKLEEN OXY can help to achieve the following credits:

Indoor Environmental Quality:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems  
IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

MR Credit 5.1 - 10% extracted and manufactured regionally  
MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

Other environmental data:

- Low VOC formula
- Biodegradable
- In conformity with OCDE 301 E rule
- Meets Terra Choice / Écologo specifications
- Paint & varnish remover CCD: 1051

## Caution



Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

## Health and Safety

Refer to the MSDS on our website for handling recommendations.

## Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: [info@profixsystems.com](mailto:info@profixsystems.com)

PROFIX is a registered trademark.

La Margna Inc.  
412, St-Sacrement Québec, Québec  
G1N 3Y3 CANADA  
Tel.: (418) 688-8286  
Fax: (418) 688-2070

[www.profixsystems.com](http://www.profixsystems.com)

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010