

# SCELLIX 18%

## SOLVENT-BASED SEALER FOR GROUT

# PROFIX



### Description

SCELLIX 18% is a solvent-based, acrylic, copolymer compound that dries fast (30 minutes) to form a hard film with a semi-gloss finish.

Although SCCELLIX 18% is colourless, it accentuates the colours of treated surfaces. It is also highly resistant to acids, chemical pollutants, petroleum products, detergents, and alcohol.

#### Characteristics

- Enhances grout colour
- Provides excellent protection
- UV-proof and will not turn yellow
- Dries quickly

#### Formats

- 250 ml bottle – 24 per box
- 500 ml bottle - 12 per box
- 1L bottle – 12 per box

### Technical data @ 22°C

#### Coverage:

- 500 ml cover approximately:
  - 300 linear feet (2 coats); OR:
  - 150 ft<sup>2</sup> with 12" x 12" tiles; 1 1/4" joints

Coverage varies according to joint width, tile porosity, surface texture, and application method.

#### Shelf life

SCCELLIX 18%: 24 months following production date (stored in a dry and heated area).

### Technical notes

For prolonged use, gloves are recommended.

#### Main use

SCCELLIX 18% is used to seal certain porous surfaces such as joint grout, wood, brick or burnt granite.

### Instructions

#### Substrate preparation



Test on a small surface first to ensure suitability of coverings.


Allow new cement grout to dry for 7 to 14 days. Clean the surface properly to allow the sealer to penetrate well. Use PROFIX POLYKLEEN CRETE grout Cleaner (Not recommended for marble and limestone).

For previously sealed grout, use the appropriate PROFIX remover :

#### Use PROFIX sealer removers:


- Water-based sealer: Use NU ZONE W Stripper
- Solvent-based sealer: use NU ZONE S Stripper

#### Application



Apply SCCELLIX 18% with a paint brush or a paint roller on all dry and porous surfaces that are clean and free of oil or other products that could create a bond barrier. For the first treatment, two successive applications are recommended. Treated surfaces must be wiped during application to remove any excess sealer. Once the first coat has dried (about 15 minutes), proceed with the second application. Always apply thin coats.

## Cleaning



Use a neutral soap (pH 7-9) such as PROFIX POLYKLEEN FLOR cleaner.

## Limitations

- Keep out of reach of children
- Wear safety glasses and gloves when applying
- Volatile and flammable; take all necessary precautions and keep away from sources of heat or flames
- Contains solvent, use in a well-ventilated area
- For outdoor installations, the temperature must not drop below 10°C at the time of installation and for a period of 24 hours

## Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

## Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. AQUA PEARL can help to achieve the following credits:

Indoor Environmental Quality:

- IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
- IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

- MR Credit 5.1 - 10% extracted and manufactured regionally
- MR Credit 5.2 - 20% extracted and manufactured regionally

## Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010

Refer to the PROFIX website for letters of certification.

Other environmental data :

- VOC: 90%
- Biodegradable
- In conformity with OCDE 301 E rule

## Caution



May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

## Health and Safety

Refer to the MSDS on our website for handling recommendations.

## Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: [info@profixsystems.com](mailto:info@profixsystems.com)

PROFIX is a registered trademark.

La Margna Inc.  
412, St-Sacrement Québec, Québec  
G1N 3Y3 CANADA  
Tel.: (418) 688-8286  
Fax: (418) 688-2070

[www.profixsystems.com](http://www.profixsystems.com)