

STONE HD

SOLVENT-BASED SEALER FOR TILES

PROFIX



Description

Solvent-based sealer available in three different finishes

STONE HD: Dense surface sealer – glossy
STONE HD: Dense surface sealer – silk
STONE HD: Dense surface sealer – natural

STONE HD is a range of solvent-based sealers (mineral essence that releases a mild odour) for porous surfaces. Sealers enhance natural colour and leave either a shiny or a mat finish. They are highly resistant to water, grease and oil.

Characteristics

- Faint odour
- Optimal protection

Formats

STONE HD - glossy:
500ml bottle - 12 per box / 1L bottle – 12 per box / 4L bottles - 4 per box

STONE HD - silk:
500ml bottle - 12 per box / 1L bottle – 12 per box / 4L bottles - 4 per box

STONE HD - natural:
500ml bottle - 12 per box / 1L bottle – 12 per box / 4L bottles - 4 per box

Technical data @ 22°C

Coverage: 1L covers approximately 150-200 ft² (varies depending on tile porosity)

Shelf life

STONE HD: 24 months following production date (stored in a dry and heated area)

Technical notes

For prolonged use, gloves are recommended.

Main use

For residential or commercial use, indoors and outdoors. Ideal for sealing Mexican tiles, concrete and cement, porous Chinese slate, granite and textured marble, quartz-resin and marble-resin composite stone, mortar joints, cement grout and sandstone.

Instructions

Substrate preparation


Test on a small surface first to ensure suitability of coverings.

Allow new cement grout to dry for 7 to 14 days. Clean the surface properly to allow the sealer to penetrate well. Use PROFIX POLYKLEEN CRETE cleaner for grout residues (not recommended for marble and limestone).

For previously sealed grout, use the proper PROFIX remover:

- Water-based sealer: use NU ZONE W stripper
- Solvent-based sealer: use NU ZONE S stripper

Application



Spread using a paint roller or a paint brush. Do not use a sponge roller as bubbles and excess will appear on the surface after drying. For best results, apply thin uniform coats. 1 to 2 coats are usually sufficient for most surfaces. Allow to dry 4 to 16 hours between each application. Allow normal circulation after 24 hours.

Cleaning



Use a neutral soap (PH 7-9) such as PROFIX POLYKLEEN FLOR cleaner. Use a ramble or white pads if using an automatic machine.

Limitations

- Keep out of reach of children
- Wear safety glasses and gloves when applying
- Flammable product; do not use near heat source
- Avoid spilling in sewers and water mains
- For outdoor installations, the temperature must not drop below 10°C at the time of installation and for a period of 24 hours

Warranty

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

Environmental data



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. STONE HD can help to achieve the following credits:

Indoor Environmental Quality:

- IEQ Credit 3.2 option 3 - Reduce indoor air quality problems
- IEQ Credit 4.1 - Low Emitting Materials

Materials and Resources:

- MR Credit 5.1 - 10% extracted and manufactured regionally
- MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

Other environmental data:

- VOC: 80gr / 100ml

Liability

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications.

May 18th, 2010

Caution



Flammable product, contains mineral spirits. Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses and a breathing mask with filters against organic vapors is recommended during interior applications. Before proceeding test first on a small non visible area to assure safe use, suitability results.

Health and Safety

Refer to the MSDS on our website for handling recommendations.

Technical support

Questions? Call the PROFIX customer care team toll-free at: 1-800-463-6850 or e-mail us at: info@profixsystems.com

PROFIX is a registered trademark.

La Margna Inc.
412, St-Sacrement Québec, Québec
G1N 3Y3 CANADA
Tel.: (418) 688-8286
Fax: (418) 688-2070

www.profixsystems.com