

# POLYKLEEN 9006

## ACID-BASED CLEANER FOR JOINTS



### DESCRIPTION

POLYKLEEN 9006 is a concentrated acid-based cleaner for grout joints and cement. It removes grease, oil, mould, dirt and old grout stains, and can be used on a variety of tiles.

### CHARACTERISTICS

- Restores appearance of grout joints
- Excellent grease cleaner
- Removes efflorescence (white powdery deposit on joints)
- pH: 1.2

### FORMATS

- 500 ml bottle – 12 per box
- 1 L bottle – 12 per box

### TECHNICAL DATA AT 22°C

### COVERAGE

Depends on type of cleaning to be done.

### USAGE FREQUENCY

Subject to the frequency of cleaning and the types of products used.

### SHELF LIFE

24 months following production date. Must be stored in a dry and heated area.

### TECHNICAL NOTES

It is very important to dilute this product with water; otherwise it could burn the cement and the grout joint.

STANDARD CLEANING: 50% 9006 / 50% water.

MAXIMUM CONCENTRATION FOR CEMENT: 70% 9006 / 30% water.

### USAGE

Test on a small surface first to ensure the product's suitability.

- Ceramic tiles
- Grout
- Brick
- Concrete


### INSTRUCTIONS

#### SUBSTRATE PREPARATION




Ensure that the surface is suitable for cleaning with an acid-based cleaner. As the product has a strong odour, you must plan a good ventilation.

#### APPLICATION



Test first on a small surface to assure suitability of coverings. It is really important to dilute with water or else the actual product could affect the cement as well as the grout.

#### CLEANING



Once cleaning is complete, rinse the entire surface thoroughly with water.

### LIMITATIONS

- Do not use on marble or limestone
- Might remove tile sealer
- Avoid freezing

## WARRANTY

The above information is accurate. However, as we have no control over conditions of use, we cannot assume any legal or other responsibility for the outcome and/or any harm that may ensue.

## LEED



Leadership in Energy & Environmental Design (LEED) is a green building rating system that plans, develops, compares and certifies sustainable buildings around the planet. The Canada Green Building Council certifies the project in terms of total points obtained after verifications and an examination of the documentation submitted by the design and construction teams. Ceraflex can help to achieve the following credits.

### INDOOR ENVIRONMENTAL QUALITY:

IEQ Credit 3.2 option 3 - Reduce indoor air quality problems

IEQ Credit 4.1 - Low Emitting Materials

### MATERIALS AND RESOURCES:

MR Credit 5.1 - 10% extracted and manufactured regionally

MR Credit 5.2 - 20% extracted and manufactured regionally

Refer to the PROFIX website for letters of certification.

### OTHER ENVIRONMENTAL DATA:

- Biodegradable
- In conformity with OCDE 301 E rule
- Meets Terra Choice / Écologo specifications
- Bathroom cleaner CCD: 146J

## CAUTION



Keep out of reach of children. May irritate eyes. Do not get in eyes. Do not swallow. Wearing of gloves and safety glasses is recommended during application.

## HEALTH AND SAFETY

Refer to the MSDS on our website for handling recommendations.

### LIABILITY

Before using, the user shall determine the suitability of this product for its intended use and the user alone shall assume all risks and liabilities in connection therewith. La Margna Inc. shall not accept any liability for any damage, loss or prejudice resulting from the direct or indirect use of our product in non-compliance to our specifications. • April 12, 2017

For questions, please contact our customer service PROFIX toll free: 1-800-463-6850 or [info@profixsystems.com](mailto:info@profixsystems.com).

PROFIX is a registered trademark.

LA MARGNA INC.

412, Saint-Sacrement, Quebec (Quebec) G1N 3Y3 CANADA

T (418) 688-8286

F (418) 688-2070

[www.profixsystems.com](http://www.profixsystems.com)